

e-STUDIO388CP

Datasheet

- > The e-STUDIO388CP is ideal for workgroups that require an efficient document output of up to 38 pages per minute.
- > This robust A4 colour printer executes large print jobs with a maximum paper capacity of up to 1,451 sheets.
- > Intuitive access to all functions and features via the colour touch panel – all at just the swipe of a finger.
- > Boost your productivity levels while enjoying the quality of each print.



The e-STUDIO388CP is a robust A4 colour printer which leaves nothing to desire, thanks to its efficiency, reliability and adaptability. A resolution of up to 1,200 x 1,200 dpi not only provides a magnificent document output with crystal-clear images, but also ensures a consistent print quality from the first to the last print.

Mobile printing capabilities offer the flexibility that is required by today's modern businesses. Clever options and solutions can tailor this device to your individual requirements, helping you to enhance your productivity and streamline your workflows.

Cutting edge technology ensures your colour print job does not come to a halt, simply select to continue printing in monochrome instead. At Toshiba, we care about respecting the environment. That is why our systems comply with today's most stringent environmental standards and have settings that can help save valuable resources.

SPECIFICATIONS

General

Print & Copy Speed	38 ppm
Warm-up Time	~ 15 seconds (from sleep mode)
Paper Size & Weight	Cassette: A6-A4/custom, 60-176 g/m ² Bypass: 76 x 127 mm - 216 x 356 mm, 60-176 g/m ²
Paper capacity	Cassette: 1x 250 sheets Max.: 1,451 sheets
Inner Output Tray	125-sheet capacity
Automatic Duplex	A4/custom, 60-105 g/m ²
Control Panel	10.9 cm (4.3") colour touch panel
Memory	Standard: 1 GB Max.: 1 GB
Interface	10Base-T/100Base-TX/1000Base-T (incl. IPv6), High Speed USB 2.0, WLAN ¹⁾ (IEEE802.11 ac/a/b/g/n)
Dimension & Weight	442 x 421 x 308 mm (W x D x H), ~ 21.1 kg
Initial Consumables	Starter Toner and Imaging Unit

Print

Resolution	Max. 1,200 x 1,200 dpi
First Print Output Time	~ 7 seconds
Page Description Language	PCL 5, PCL 6 emulation, PostScript 3 and PDF v1.7 emulation, XPS, PPDS
Supported Systems	Windows 10/8/8.1/7, Windows Server 2016/Server 2012/Server 2008 (32/64 bit), Windows Server 2012 R2/Server 2008 R2 (64 bit), Mac OS X 10.6-10.13, Linux/Unix, Novell NetWare, Citrix, SAP
Mobile Printing	AirPrint, Mopria Print Service, Google Cloud Print
Print Functions	Universal Printer Driver, Print from USB, Multiple pages per sheet, Envelope printing

System & Security

Device Management	e-BRIDGE Fleet Management System ¹⁾
System Features	Energy saving modes, Automatic toner saturation/colour calibration
Accounting & Security	Private print, IP address filter, Port filter, Support of SNMPv3, SSL and IPSec protocols, 802.1x authentication ¹⁾ , Operator panel lock ²⁾ , Disk wipe ²⁾

Options

550-sheet Drawer	550-sheet capacity, A5-A4, 60-176 g/m ²
650-sheet Duo-drawer	1x cassette, 550-sheet capacity, A5-A4, 60-176 g/m ² 1x bypass, 100-sheet capacity, A6-A4, 60-176 g/m ²
Swivel Cabinet	
Adjustable Printer Stand	
User Flash Memory	
Hard Disk Drive	
Wireless LAN Module	
Forms & Barcode Card	
PRESCRIBE Card	
Security Element	

¹⁾ Optional

²⁾ Requires optional HDD



Toshiba Tec Germany Imaging Systems GmbH

Carl-Schurz-Str. 7
41460 Neuss
Germany

Telephone
+49 2131-1245-0

Website
www.toshibatec.eu

